

TOSHIBA
Leading Innovation >>>

TDP-SPI
TDP-XP1
TDP-XP2

Making Brighter

and Sharper Impression that Lasts



Toshiba's SP-1, XP-1 & XP-2 are effective projectors packed with great values. These light-weight projectors offer up to an outstanding 2,500 ANSI lumens, display XGA 1024 x 768 resolution with an ultra-sharp contrast ratio of 2000:1, and a long lamp life of 4000 hours. Incorporated with DLP Brilliant Color™ technology, the projectors allow professionals, teachers, corporate executives to proudly project their presentations with fabulous results. The range is also a great companion for enjoyable digital home entertainment after a hard day's work.



DLP • High Contrast Ratio 2,000:1 • SXGA (Compressed)

Specifications

| Model | | TDP-SPI | TDP-XPI | TDP-XP2 |
|-------------------------------------|-----------------------|------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| Display Technology | Panel Size | 0.55" DMD | 0.55" DMD | 0.55" DMD |
| | Aspect Ratio | 4:3 Switchable To 16:9 | 4:3 Switchable To 16:9 | 4:3 Switchable To 16:9 |
| Resolution | | SVGA (800 x 600) | XGA (1024 x 768) | XGA (1024 x 768) |
| Brightness | | 2,200 ANSI Lumens | 2,200 ANSI Lumens | 2,500 ANSI Lumens |
| Contrast Ratio | | 2,000:1 | 2,000:1 | 2,000:1 |
| Projection Lens | Optical Zoom | Manual Zoom | Manual Zoom | Manual Zoom |
| | Zoom Ratio | 1.1x Manual Zoom | 1.1x Manual Zoom | 1.1x Manual Zoom |
| Light Source | | 180/150W | 180/150W | 180/150W |
| Compatible Scanning Frequency | Horizontal | 31.4kHz-68.7kHz | 31.4kHz-68.7kHz | 31.4kHz-68.7kHz |
| | Vertical | 56Hz -85Hz | 56Hz -85Hz | 56Hz -85Hz |
| Keystone Correction | | Manual | Manual | Manual |
| Picture Color Enhancer | | BrilliantColor™ | BrilliantColor™ | BrilliantColor™ |
| Projection Screen Size (Diagonal) | | 23.9" - 300" | 23.9" - 300" | 23.9" - 300" |
| Projection Distance for 100" screen | | 3.98m(wide)-4.41m(Tele) | 3.98m(wide)-4.41m(Tele) | 3.98m(wide)-4.41m(Tele) |
| Input Terminal | RGB | x 1: D-sub 15 Terminal | x 1: D-sub 15 Terminal | x 1: D-sub 15 Terminal |
| | S-Video | x 1: S Terminal | x 1: S Terminal | x 1: S Terminal |
| | Composite Video | x 1: RCA Terminal | x 1: RCA Terminal | x 1: RCA Terminal |
| | RGB Audio | x 1: Stereo Mini Jack | x 1: Stereo Mini Jack | x 1: Stereo Mini Jack |
| Output Terminal | RGB | x 1: D-sub 15 Terminal (Shared with IN/OUT) | x 1: D-sub 15 Terminal (Shared with IN/OUT) | x 1: D-sub 15 Terminal (Shared with IN/OUT) |
| | Audio | x 1: Stereo Mini Jack (Variable output level) | x 1: Stereo Mini Jack (Variable output level) | x 1: Stereo Mini Jack (Variable output level) |
| Other Terminal | RS-232C(D-Sub 9pin) | Yes | Yes | Yes |
| | USB | No | No | No |
| Other Terminal | Video | NTSC, PAL, SECAM | NTSC, PAL, SECAM | NTSC, PAL, SECAM |
| | Color difference | 480i, 480p, 576i, 576p, 720p, 1080i | 480i, 480p, 576i, 576p, 720p, 1080i | 480i, 480p, 576i, 576p, 720p, 1080i |
| | RGB | VGA, SVGA (True), XGA, SXGA (Compressed) | VGA, SVGA, XGA (True), SXGA (Compressed) | VGA, SVGA, XGA (True), SXGA (Compressed) |
| Lamp | Type (Standard / Low) | 180W / 150W | 200W / 150W | 200W / 150W |
| | Life (Standard / Low) | 3,500H / 4,000H | 3,000H / 4,000H | 3,000H / 4,000H |
| Power Consumption | | 250W | 280W | 280W |
| Power Source | | AC 100-240V (50/60Hz) | AC 100-240V (50/60Hz) | AC 100-240V (50/60Hz) |
| Replacement Lamp | | TLP-LV9 | TLP-LV10 | TLP-LV10 |
| Internal Speaker | | 2W (Mono) | 2W (Mono) | 2W (Mono) |
| Dimensions (WxHxD) | | 270 x 87 x 189 mm | 270 x 87 x 189 mm | 270 x 87 x 189 mm |
| Weight | | 2.2kg | 2.2kg | 2.2kg |
| Noise Level | | 34 dB(Normal Mode)/ 30 dB(Eco Mode) | 34 dB(Normal Mode)/ 30 dB(Eco Mode) | 34 dB(Normal Mode)/ 30 dB(Eco Mode) |
| OSD Languages | | English, Chinese(Simplified/ Traditional), Indonesian and Other Languages | English, Chinese(Simplified/ Traditional), Indonesian and Other Languages | English, Chinese(Simplified/ Traditional), Indonesian and Other Languages |
| Accessories | | Simple Remote Controller And Batteries, D-sub 15pin Cable, AC Cable, Carrying Case | Simple Remote Controller with Batteries, D-sub 15pin Cable, AC Cable, Carrying Case | Simple Remote Controller with Batteries, D-sub 15pin Cable, AC Cable, Carrying Case |

Product design and specifications are subject to change without notice.



Making Brighter and Sharper Impression that Lasts

TOSHIBA

TOSHIBA SINGAPORE PTE., LTD.

Distributor and Trader Department - Asian Headquarters Division
438B Alexandra Road #06-01, Alexandra Technopark Singapore 119968
Tel (65) 6275 0660 Fax: (65) 6275 5053
<http://projectors.toshiba.com.sg>

Distributed by: